



VALVE NOTES:

- BRASS FULL PORT BALL VALVE
- 29" HG -600PSI WOG ,COLD NON-SHOCK
- BLOW OUT PROOF STEM WITH ADJUSTABLE STEM PACKING
- TEMPERATURE -20°F TO 400°F
- PLATED BRASS BALL
- STEEL HANDLE
- **TEFLON SEATS**
- NPT THREADS STANDARD

SEE CATALOG FOR OPTIONS AND ORDERING DETAILS

PART	NPT	Α	В	C	D	Cv	
BGF-2	1/4"	1.64	1.78	3.30	0.38	6	
BGF-3	3∕8"	1.69	1.89	3.22	0.39	7	
BGF-4	况"	2.12	2.06	4.36	0.58	19	
BGF-6	3/4"	2.47	2.11	4.06	0.76	34	
BGF-8	1"	2.82	2.47	5.09	0.95	50	
BGF-10	1 1/4"	3.03	3.02	5.36	1.24	110	
BGF-12	1 ½"	3.70	3.20	5.76	1.58	268	
BGF-16	2"	4.46	3.45	6.40	1.97	309	
SEE BGF-C SERIES FOR SIZES 2 1/4" TO 4"							

DRAWING NAME:								
BRASS FULL PORT 2-WAY BALL VALVES								
MATERIAL:	DRAWING NUMBER: BGF-SERIES	REV.						
SCALE: N.T.S.	NAME: MCH DATE:	8-9-19						

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNILESS OTHERWISE AGREED UPON IN WRITING.

PALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.