



PRESSURE SETTINGS																
<b>PSI</b>	80	90	100	110	115	125	135	145	150	165	175	180	190	200	215	225
<b>SCFM</b>	28	31	34	37	39	42	46	48	50	54	57	59	62	65	69	72
* SCFM AT 60 DEGREES F - 10% ACCUMULATION (SET PRESSURE X 1.1)+14.7 X .276 = FLOW (SCFM)																

MATERIALS	
BODY	BRASS
SPRING	STAINLESS STEEL
SEAL	SILICON (STD)
RATINGS:	UNFIRED PRESSURE VESSEL, ASME, NB, UV, CRN# 03378.0-9
OPTIONS:	VITON (SEAL)
TEMP RANGE	-65°F TO 250°F

NOTES:  
 TO ORDER A SPECIFIC RANGE, ADD SET PRESSURE TO END OF PART NUMBER.  
 EXAMPLE:  
 125 PSI SET PRESSURE WILL BE 'CVM1-125'. TO ORDER THIS SAME VALVE WITH VITON SEAT, ADD 'V' TO END OF NUMBER. 'CVM1-125V'

CONSULT CATALOG OR FACTORY FOR ADDITIONAL SIZES, MATERIALS, AND CUSTOM ORDER REQUESTS



DRAWING NAME:  
**1/8" NPT BRASS CODE RELIEF VALVE**

<b>MATERIAL:</b>	<b>A</b>	<b>DRAWING NUMBER:</b> CVM1-**	<b>REV.</b> <b>2</b>
<b>SCALE: N.T.S.</b>	<b>NAME: MCH</b>	<b>DATE: 10-13-17</b>	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.  
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.  
 \*ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.\*