



PRESSURE SETTINGS																
PSI	80	90	100	110	115	125	135	145	150	165	175	180	190	200	215	225
SCFM	28	31	34	37	39	42	46	48	50	54	57	59	62	65	69	72
* SCFM AT 60 DEGREES F - 10% ACCUMULATION (SET PRESSURE X 1.1)+14.7 X .276 = FLOW (SCFM)																

NOTES:

- BRASS BODY
- STAINLESS STEEL SPRING
- SILICONE SEAL STANDARD
- VITON SEAL, 'V' SUFFIX, (OPTIONAL)
- UNFIRED PRESSURE VESSEL
- ASME, NB, UV & CRN# 03378.0-9
- TEMPERATURE -65°F TO 250°F

NOTE:

PART NUMBER DATA

PN: CVM2-*

PRESSURE SETTING
80 TO 225 PSI
IN 5 PSI INCREMENTS

CONSULT CATALOG OR FACTORY FOR ADDITIONAL SIZES,
MATERIALS, AND CUSTOM ORDER REQUESTS



DRAWING NAME:

1/4" NPT BRASS CODE RELIEF VALVE

MATERIAL:

A

DRAWING NUMBER:

CVM2-**

REV.

1

SCALE: N.T.S.

NAME: MCH

DATE: 1-1-17