

2X PG-11 CONNECTION

VALVE NOTES:

- CARBON STEEL OR STAINLESS STEEL (SEE ORDERING MATRIX)
- 3000 PSI WORKING PRESSURE
- BLOW-OUT PROOF STEM
- VITON STEM O-RING
- TEMPERATURE: -20°F to 185° F
- 2" NPT SIZE IS STANDARD PORT ALL OTHERS FULL PORT

ACTUATOR NOTES:


- IP67 RATED
- 2 LIMIT SWITCHES : STD
- INTERNAL HEATER: STD
- HIGH IMPACT ABS ACTUATORS LISTED AS STANDARD, METAL HOUSING UNITS AVAILABLE UPON REQUEST.
- -4°F TO 131°F

REFER TO CATALOG FOR FURTHER ORDERING INFORMATION

ASSEMBLY DIMENSIONS- STAINLESS STEEL (S2F3M)								
PART #	ACTUATOR MODEL#		A	B	C	D	E	B ^M
	STANDARD	OPTIONAL METAL						
E***/*2F3M-2	VB015	VB030M	2.51	7.18	4.84	6.41	1/4 NPT	9.64
E***/*2F3M-3	VB015	VB030M	2.51	7.18	4.84	6.41	3/8 NPT	9.64
E***/*2F3M-4	VB030	VB030M	2.57	9.01	6.18	7.48	1/2 NPT	9.65
E***/*2F3M-6	VB030	VB030M	3.11	9.12	6.18	7.48	3/4 NPT	9.75
E***/*2F3M-8	VB030	VB030M	3.38	9.88	6.18	7.48	1 NPT	10.14
E***/*2F3M-10	VB060	VB060M	4.13	10.78	7.28	8.43	1 1/4 NPT	11.04
E***/*2F3M-12	VB060	VB060M	4.68	11.42	7.28	8.43	1 1/2 NPT	11.68
E**/*S2S3M-16	VB060	VB060M	5.23	11.42	7.28	8.43	2 NPT	11.68

*115V = 115VAC
 *240V = 240 VAC
 *012D = 12VDC
 *024D = 24VDC
 B^M = OPTIONAL METAL ACTUATOR

*2F3M:
 S2F3M = STAINLESS STEEL
 C2F3M = CARBON STEEL



DRAWING NAME:

ACTUATED VALVES:
 E***- C2F3M-S2F3M Series

MATERIAL:	A	DRAWING NUMBER: E-ACT-C2F3M-S2F3M	REV. 3
SCALE: N.T.S.	NAME: MCH	DATE: 2-5-20	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING. *ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.*