



**VALVE NOTES:**

- CF8M STAINLESS STEEL BODY
- 316 STAINLESS BALL
- 29" Hg-2C000 PSIG WOG COLD NON-SHOCK
- BLOWOUT PROOF STEM
- RTFE SEATS
- TEMP -20° TO 450° F

**ACTUATOR NOTES:**

- IP67 RATED
- 2 LIMIT SWITCHES : STD
- INTERNAL HEATER: STD
- HIGH IMPACT ABS ACTUATORS LISTED AS STANDARD, METAL HOUSING UNITS AVAILABLE UPON REQUEST.
- -4°F TO 131°F

REFER TO CATALOG FOR FURTHER ORDERING INFORMATION



**DRAWING NAME:**  
ELECTRIC ACTUATED 2000 PSI 2-WAY STAINLESS STEEL  
2-WAY STD. PORT VALVES

<b>MATERIAL:</b>	<b>A</b>	<b>DRAWING NUMBER:</b> E-ACT-S2S	<b>REV.</b> 3
<b>SCALE:</b> N.T.S.	<b>NAME:</b> MCH	<b>DATE:</b> 8-1-2024	

ASSEMBLY DIMENSIONS- STAINLESS STEEL (S2S)									
PART #	ACTUATOR MODEL		A	B	C	D	E	B <sup>M</sup>	BRACKET/ COUPLER
	STD	OPTIONAL							
E**/S2S-2	VB015	VB030M	2.00	8.64	4.84	6.41	1/4 NPT	11.10	MK2051
E**/S2S-3	VB015	VB030M	2.00	8.64	4.84	6.41	3/8 NPT	11.10	MK2051
E**/S2S-4	VB015	VB030M	2.40	9.07	4.84	6.41	1/2 NPT	11.53	MK2051

\*115V = 115VAC  
\*240V = 240 VAC  
\*012D = 12VDC  
\*024D = 24VDC  
B<sup>M</sup> = OPTIONAL  
METAL ACTUATOR