

VALVE NOTES:


- ASTM 316 STAINLESS STEEL CONSTRUCTION
- POLISHED DISC ENSURES SMOOTH FLOW AND REDUCED BUILDUP
- SURFACE FINISH MEETS ALL 3-A, FDA AND USDA STANDARDS AND REQUIREMENTS
- SILICONE SEATS STANDARD, EPDM, VITON AND WHITE VITON AVAILABLE
- 110PSI @ 200° F
- AVAILABLE AS MANUAL VALVE WITH POSITON-LOCKING HANDLE

ACTUATOR NOTES:

- HOUSING MATERIAL : ABS (STD)
- ALUMINUM HOUSING OPTIONAL
- OPERATING TEMP: -4° TO 131° F
- 2 LIMIT SWITCHES INTERNAL, STD
- INTERNAL HEATER, STD
- BATTERY BACKUP OPTIONAL
- 4-20 FEEDBACK OPTIONAL

ELECTRIC ACTUATED STAINLESS TRI-CLAMP BUTTERFLY VALVE							
PART #	ACT	A	B	C	D	E	B ^M
E ^{***} /SSST-1	VB030	3.50	10.32	6.18	7.48	0.87	10.95
E ^{***} /SSST-1.5	VB030	3.50	10.55	6.18	7.48	1.37	11.18
E ^{***} /SSST-2	VB030	3.75	11.13	6.18	7.48	1.87	11.76
E ^{***} /SSST-2.5	VB030	3.81	11.52	6.61	6.61	2.37	12.15
E ^{***} /SSST-3	VB030	4.06	11.77	6.18	7.48	2.84	12.40
E ^{***} /SSST-4	VB060	4.78	12.92	7.28	8.43	3.84	13.18
E ^{***} /SSST-6	VB110	6.00	14.6	8.31	9.33	5.83	15.11

*115V = 115VAC
 *240V = 240 VAC
 *012D = 12VDC
 *024D = 24VDC
 B^M = OPTIONAL METAL ACTUATOR



THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING. *ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.*

CONSULT ORDERING MATRIX FOR OPTIONS AND MATERIALS



DRAWING NAME:
ELECTRIC-ACTUATED SANITARY TRI-CLAMP BUTTERFLY VALVE

MATERIAL:	A	DRAWING NUMBER: E-ACT-SST-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 12-1-16	