


NOTES::

HIT SERIES

- CLEAR ANODIZED ALUMINUM
 - 25 MICRON SINTERED BRONZE ELEMENT
 - 5000 PSIG (HYDRAULIC ONLY) MAX.WORKING PRESSURE
 - BUNA-N SEALS 35°F TO 200°F
- OPTIONS:
- VITON SEALS, SUFFIX "V" 35°F TO 400°F
 - MICRON SIZE, SUFFIX "10", "40", "90"
 - (EXAMPLE HIT-290), (KIT EXAMPLE EK2-90)
 - AVAILABLE IN STAINLESS STEEL

PART #	SIZE	SEAL MATERIAL
HIT-2	1/4 NPT	BUNA
HIT-2V	1/4 NPT	VITON
HIT-3	3/8 NPT	BUNA
HIT-3V	3/8 NPT	VITON
HIT-S6	SAE-6 (9/16)	BUNA
HIT-S6V	SAE-6 (9/16)	VITON



DRAWING NAME: T-TYPE INLINE HYDRAULIC FILTER			
MATERIAL: --	A	DRAWING NUMBER: HIT-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 9/5/2019	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
 EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.