



- MATERIALS:**
- BODY: ANODIZED 6061-T6
  - SPOOL: 6061-T6
  - SEALS: BUNA-N
  - ARMATURE MOUNT: ACETAL PLASTIC
  - OVER-RIDE BUTTON: 6061-T6
  - ARMATURE TUBE: BRASS/STEEL
  - RETAINING NUT: ACETAL PLASTIC WITH PLATED STEEL THREADED INSERT
  - BODY END PLATE AND SCREWS: PLATED STEEL
  - PRE-WIRING OPTION: ADD '-W' TO PART NUMBER AFTER THE VOLTAGE.
- EXAMPLE:**  
 PRE WIRED: 'N4S-C1-W'  
 NON-WIRED (STD) : 'N4S-C1'

MODEL	VOLTAGE	INRUSH
N4S-C1	110 VAC	62 mA
N4S-C2	24 VDC	108 mA
N4S-C12	12 VDC	204 mA
N4S-C22	220 VAC	31 mA
N4S-C24	24 VAC	C/F

**UCI**

DRAWING NAME:  
**N4S-C**

MATERIAL:	<b>A</b>	DRAWING NUMBER: N4S-C_DIM	REV. <b>4</b>
SCALE: 1:0.9.	NAME: MCH	DATE: 6-21-22	