



SET PRESSURE	SCFM
5	12
10	30
15	43
20	50
25	56
30	63
40	82
50	97
60	110
75	134

NOTES:

- MACHINED BRASS BODY, POPPET AND SLEEVE
- 302 STAINLESS STEEL SPRING
- SILICONE SEAL STD, VITON OPTIONAL ('V' SUFFIX)
- UNFIRED PRESSURE VESSEL
- TEMPERATURE 0°F TO 350°F

CRACKING PRESSURE RANGE FOR NCHL2 SERIES VALVES

PART#	MIN. CRACKING PRESSURE(PSI)	MAX. CRACKING PRESSURE(PSI)
NCHL2-5	4.50	5.50
NCHL2-10	9.00	11.00
NCHL2-15	13.50	16.50
NCHL2-20	18.00	22.00
NCHL2-25	17.50	22.50
NCHL2-30	27.00	33.00
NCHL2-35	31.50	38.50
NCHL2-40	36.00	44.00
NCHL2-45	40.50	49.50
NCHL2-50	45.00	55.00
NCHL2-55	49.50	60.50
NCHL2-60	54.00	66.00
NCHL2-65	58.50	71.50
NCHL2-70	63.00	77.00
NCHL2-75	67.50	82.50

ALL VALVES ARE MANUFACTURED TO RELIEVE WITHIN +/- 10% OF SET PRESSURE

NOTE: PART NUMBER NCHL2-*
 * = PRESSURE SETTING IN 5 PSI INCREMENTS
 EXAMPLE: NCHL2-30 = 30 PSI RELIEF



DRAWING NAME:

NCHL2-SERIES RELIEF VALVES

MATERIAL:	A	DRAWING NUMBER:	NCHL2-SERIES	REV.	1
SCALE: 4:1	NAME: MCH	DATE:	3-15-17		

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.