



PRESSURE SETTINGS																
<b>PSI</b>	80	90	100	110	115	125	135	145	150	165	175	180	190	200	215	225
<b>SCFM</b>	28	31	34	37	39	42	46	48	50	54	57	59	62	65	69	72
* SCFM AT 60 DEGREES F - 10% ACCUMULATION (SET PRESSURE X 1.1)+14.7 X .276 = FLOW (SCFM)																

**NOTES:**

- BRASS BODY
- STAINLESS STEEL SPRING
- SILICONE SEAL STANDARD
- SILICONE SEAL STANDARD (VITON SEAL, 'V' SUFFIX, OPTIONAL)
- UNFIRED PRESSURE VESSEL
- TEMPERATURE -65°F TO 250°F

NOTE:  
PART NUMBER DATA  
PN: NCM2-\*

PRESSURE SETTING  
80 TO 225 PSI  
IN 5 PSI INCREMENTS

CONSULT CATALOG OR FACTORY FOR ADDITIONAL SIZES,  
MATERIALS, AND CUSTOM ORDER REQUESTS



DRAWING NAME: NCM2-SERIES RELIEF VALVE			
MATERIAL:	A	DRAWING NUMBER: NCM2-*	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE:	2-10-17

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.  
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS  
EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN  
WRITING.  
\*ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.\*