



VALVE NOTES:
 CF8M STAINLESS STEEL BODY
 316 STAINLESS BALL
 29" Hg-2000 PSIG WOG COLD NON-SHOCK
 BLOWOUT PROOF STEM
 STANDARD PORT
 RTFE SEATS
 TEMP -20° TO 450° F

DOUBLE ACTING STAINLESS STEEL (S2S)							
PART #	ACTUATOR SIZE (mm)***	A	B	C	D	E	BRACKET/ COUPLER
PD/S2S-2	DA32	2.00	5.61	5.10	2.02	1/4 NPT	MK2050
PD/S2S-3	DA32	2.00	5.61	5.10	2.02	3/8 NPT	MK2050
PD/S2S-4	DA32	2.40	5.61	5.10	2.02	1/2 NPT	MK2050

FAILSAFE OPEN/CLOSE- STAINLESS STEEL (S2S)							
PART #	ACTUATOR SIZE (mm)***	A	B	C	D	E	BRACKET/ COUPLER
P*/S2S-2	SR52	2.00	6.60	5.88	2.82	1/4 NPT	MK2051
P*/S2S-3	SR52	2.00	6.60	5.88	2.82	3/8 NPT	MK2051
P*/S2S-4	SR52	2.40	6.60	5.88	2.82	1/2 NPT	MK2051

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
 EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

P* = FAILSAFE CLOSE
 PO = FAILSAFE OPEN



DRAWING NAME:
 PNEUMATIC ACTUATED 2000 PSI 2-WAY STAINLESS STEEL
 2-WAY STD. PORT VALVES

MATERIAL:	A	DRAWING NUMBER: P-ACT-S2S	REV. 3
SCALE: N.T.S.	NAME: MCH	DATE: 8-1-2024	