


SIZE	A	B	C	ØE	Cv	TORQUE (in. lbs.)
1/4"	2.00	1.97	3.78	0.38	6	30
3/8"	2.00	1.97	3.78	0.46	7	30
1/2"	2.40	1.97	3.78	0.50	10	40
3/4"	2.67	2.09	3.78	0.59	16	60
1"	3.26	2.52	4.92	0.79	24	115
1 1/4"	3.54	2.60	4.92	1.00	47	160
1 1/2"	4.09	3.10	6.70	1.26	90	220
2"	4.60	3.27	6.70	1.50	125	300

VALVE NOTES:

- CF8M STAINLESS STEEL BODY
- 316 STAINLESS BALL
- 29" Hg-2000 PSIG WOG COLD NON-SHOCK
- BLOWOUT PROOF STEM
- STANDARD PORT
- RTFE SEATS
- TEMP -20° TO 450° F
- CAN BE ACTUATED WITH REQUIRED MOUNTING BRACKET. CONSULT CATALOG
- FOR DETAILS OR CALL FACTORY

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
 EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

			
DRAWING NAME: 2000 PSI STAINLESS STEEL 2 WAY MANUAL VALVE			
MATERIAL:	A	DRAWING NUMBER: S2S-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 7/18/2018	