



SFM SERIES HIGH PRESSURE VALVES: DIMENSIONS								
SIZE	PART#	THREAD	PSI	A	B	C	D	ØE
1/4"	SFM-2	1/4" NPT	5880	2.72	1.20	4.21	1.02	0.24
	SFM-S4	7/16"-20 ORB						
3/8"	SFM-3	3/8" NPT	5880	2.87	1.29	4.21	1.26	0.39
	SFM-S6	9/16"-18 ORB						
1/2"	SFM-4	1/2" NPT	5880	3.62	1.31	4.21	1.38	0.51
	SFM-S8	3/4"-16 ORB						
3/4"	SFM-6	3/4" NPT	5145	3.82	1.91	6.50	1.93	0.79
	SFM-S12	1 1/8"-12 ORB						
1"	SFM-8	1" NPT	5145	4.45	1.95	6.50	2.36	0.94
	SFM-S16	1 1/8"-12 ORB						
1 1/4"	SFM-10	1 1/4" NPT	5880	6.54	2.59	8.30	3.54	1.25
	SFM-S20	1 5/8"-12 ORB						
1 1/2"	SFM-12	1 1/2" NPT	5880	7.14	2.73	8.30	3.26	1.49
	SFM-S24	1 7/8"-12 ORB						
2"	SFM-16	2" NPT	5880	9.30	3.15	8.50	3.94	1.89
	SFM-S32	2 1/2"-12 ORB						

VALVE NOTES:

- HIGH PRESSURE APPLICATIONS
- 316 STAINLESS STEEL CONSTRUCTION
- BLOWOUT-PROOF STEM
- DELRIN SEATS
- VITON O-RINGS
- TEMP: -20° TO 216° F
- LOCKING PLATE OPTION AVAILABLE
- ACTUATED VERSION AVAILABLE

PLEASE CONSULT CATALOG FOR FURTHER ORDERING INFORMATION AND OPTIONS



DRAWING NAME:

HIGH PRESSURE 2-WAY STAINLESS STEEL BALL VALVE WITH HANDLE

MATERIAL:

A

DRAWING NUMBER:
SFM-SERIES

REV.
1

SCALE: N.T.S.

NAME: MCH

DATE: 1-11-17