



**VALVE NOTES:**

- CF8M STAINLESS FULL PORT BALL VALVE
- 29" HG -1000PSI WOG
- BLOW OUT PROOF STEM
- LOCKING HANDLE (STANDARD)
- TEMPERATURE -20°F TO 400°F
- RPTFE SEATS, PTFE SEALS

SEE CATALOG FOR OPTIONS AND ORDERING DETAILS

PART	NPT	A	B	C	D	Cv
SGF-2	1/4"	2.00	2.30	3.94	0.46	6
SGF-3	3/8"	2.00	2.30	3.94	0.49	6
SGF-4	1/2"	2.28	2.30	3.94	0.59	18
SGF-6	3/4"	2.58	2.50	4.92	0.79	34
SGF-8	1"	3.10	3.07	5.87	0.98	49
SGF-10	1 1/4"	3.54	3.27	5.87	1.26	103
SGF-12	1 1/2"	4.13	4.02	7.48	1.50	266
SGF-16	2"	4.88	4.25	7.48	1.97	307
SGF-20	2 1/2"	5.75	5.43	9.84	2.48	C/F
SGF-24	3"	6.46	5.75	9.84	2.99	C/F
SGF-32	4"	9.45	6.89	11.81	3.94	C/F



DRAWING NAME:  
**STAINLESS STEEL FULL PORT 2-WAY  
 BALL VALVES**

MATERIAL:	A	DRAWING NUMBER: SGF-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 1-16-17	