



DIMENSIONS				
PART#	A	B	C	NPT
SSCVH2-*	1.74	0.68	0.25	1/4"
SSCV4-*	2.69	0.87	0.39	1/2"
SSCV6-*	3.69	1.06	0.53	3/4"

SPECIFICATIONS	
BODY	ASTM B-16 STAINLESS
SPRING	304 STAINLESS STEEL
SEAL	VITON
RATINGS:	ASME, UB, UV & CRNUNFIRED PRESSURE VESSEL
OPTIONS:	VITON (SEAL)
TEMP RANGE	0°F TO 350°F
PRESSURES	25 TO 300 PSIG
ACCURACY	±3% OF SET PRESSURE ±2% UNDER 70 PSI

NOTE:
 USE SUFFIX TO SPECIFY SET PRESSURE.
 EXAMPLE: "SSCV6-50" = 3/4" NPT VALVE SET TO 50PSI

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

DRAWING NAME: SSCV AND SSCVH2-SERIES STAINLESS STEEL RELIEF VALVES			
MATERIAL:	A	DRAWING NUMBER: SSCV-SSCVH2-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE:	2-17-20