



SSWC SERIES DIMENSIONS AND FLOW					
PART #	A	B	C	D	CV
SSWC-4	2.56	1.65	0.59	1/2 NPT	9.00
SSWC-6	3.15	2.01	0.79	3/4 NPT	16.60
SSWC-8	3.54	2.36	0.98	1 NPT	27.00
SSWC-10	4.13	2.60	1.26	1 1/4 NPT	45.00
SSWC-12	4.72	2.95	1.57	1 1/2 NPT	72.40
SSWC-16	5.51	3.15	1.97	2 NPT	118.90
SSWC-20	7.13	3.90	2.56	2 1/2 NPT	C/F
SSWC-24	7.87	4.09	3.15	3 NPT	C/F

VALVE NOTES:

- 200 PSI MAX WORKING PRESSURE-4°F TO 356°F
- BODY, CAP, DISC: ASTM A351 CF8M STAINLESS
- PIN: 316 STAINLESS
- PLUG: 316 STAINLESS
- BODY SEAL: PTFE
- PRESSURE TEST: API 598



DRAWING NAME:
**SSWC SERIES STAINLESS STEEL 2-WAY NPT
 SWING CHECK VALVES**

MATERIAL:	A	DRAWING NUMBER: SSWC-SERIES	REV. 3
SCALE: N.T.S.	NAME: MCH	DATE: 10-3-17	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
 EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.