



NOTES:

1. 1000 PSI WOG
2. CF3M BODY
3. 316 STAINLESS STEEL BALL
4. 4 SEAT CONSTRUCTION
ALLOWS PRESSURE FROM ANY PORT
5. CAVITY FILLED (STD)
MEETS FDA, USDA & 3A RATINGS
6. PTFE SEATS AND CAVITY FILLER
7. VITON STEM O-RING
8. ACTUATABLE, ELECTRIC OR PNEUMATIC.
9. L-PORT AND 4 WAY VARIANTS AVAILABLE. - CONSULT FACTORY

STC SERIES 3-WAY T-PORT DIMENSIONAL DATA

SIZE	A	B	C	D	E	F (MM)	G	PORT DIA	MOUNT PATTERN
1/2	4.33	1.54	2.36	2.16	5.19	9	1.00	0.37	F03/F04
3/4	4.69	1.77	2.54	2.34	5.19	9	1.00	0.62	F03/F04
1	6.00	2.27	3.61	3.00	7.28	11	1.80	0.87	F04/F05
1-1/2	7.50	3.02	4.34	3.75	8.66	14	1.80	1.37	F05/F07
2	8.50	3.41	4.74	4.25	8.66	14	2.50	1.87	F05/F07
2 1/2	7.76	3.94	5.00	6.50	9.92	17	3.00	2.37	F07/F10
3	12.0	4.86	6.63	6.00	13.78	17	3.57	2.88	F07/F10
4	13.0	5.51	7.28	6.50	13.78	17	4.68	3.83	F07/F10

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
 ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
 ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



DRAWING NAME:

3-WAY STAINLESS STEEL SANITARY TRI CLAMP T-PORT MANUAL BALL VALVES WITH HANDLE

MATERIAL: --	A	DRAWING NUMBER: STC-TT-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 11/10/2022	