



DATA								
PART NO	A (NPT)	B	C	Cv	BODY AND CAP	ELEMENT MESH (STD)	SEAL	BLOW OFF PLUG
YSCS-2	1/4	2.93	2.37	7	ASTM B216 WEB (EPOXY COATED)	304 STAINLESS STEEL (WATER SCREEN) 0.062 (STEAM SCREEN) 0.033	SPIRAL WOUND STAINLESS STEEL	CAST STEEL
YSCS-3	3/8	2.93	2.37	7				
YSCS-4	1/4	2.93	2.37	9.4				
YSCS-6	3/4	3.68	2.81	18				
YSCS-8	1	4.56	3.68	30				
YSCS-10	1 1/4	4.93	4.12	45				
YSCS-12	1 1/2	5.56	4.75	63				
YSCS-16	2	6.93	6.00	98				
YSCS-20	2 1/2	12.00	10.50	130				
YSCS-24	3	12.00	10.50	180				

NOTES:

- ANSI CLASS 600 LB
- 1480 PSI @ 100°F WOG
- 825 PSI @ 800°F WOG
- 600 PSI @ 489°F WOG
- AVAILABLE IN SOCKET WELD (CONSULT FACTORY)



DRAWING NAME:
EPOXY COATED CARBON STEEL Y-STRAINER SERIES

MATERIAL:	A	DRAWING NUMBER: YSCS-SERIES	REV. 1
SCALE: N.T.S.	NAME: MCH	DATE: 10-13-17	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.