



DATA								
PART NO	A (NPT)	B	C	Cv	BODY AND CAP	ELEMENT MESH (STD)	SEAL	BLOW OFF PLUG
YSSS-2	1/4	2.93	2.37	7	ASTM A351 CF8M/316	304 STAINLESS STEEL (WATER SCREEN) 0.062 (STEAM SCREEN) 0.033	SPIRAL WOUND STAINLESS STEEL	316 STAINLESS STEEL
YSSS-3	3/8	2.93	2.37	7				
YSSS-4	1/4	2.93	2.37	9.4				
YSSS-6	3/4	3.68	2.81	18				
YSSS-8	1	4.56	3.68	30				
YSSS-10	1 1/4	4.93	4.12	45				
YSSS-12	1 1/2	5.56	4.75	63				
YSSS-16	2	6.93	6.00	98				
YSSS-20	2 1/2	12.00	10.50	130				
YSSS-24	3	12.00	10.50	180				

NOTES:

- ANSI CLASS 600 LB
- 1440 PSI @ 100°F WOG
- 700 PSI @ 1000°F WOG
- 600 PSI @ 489°F WOG
- AVAILABLE IN SOCKET WELD (CONSULT FACTORY)



DRAWING NAME:

STAINLESS STEEL Y-STRAINER SERIES

MATERIAL:

A

DRAWING NUMBER:
YSSS-SERIES

REV.
1

SCALE: N.T.S.

NAME: MCH

DATE: 10-13-17