



**ACTUATOR NOTES:**

- 12VDC
- MANUAL OVER RIDE
- 4-20 mA POSITIONING
- 50% DUTY
- 8 SEC WORKING TIME OPEN TO CLOSE
- 2 AUX SWITCHES & HEATER: STD
- PG11 CONNECTIONS

**VALVE NOTES:**

- STAINLESS STEEL - PEICE
- 1000 PSI (250 STEAM)
- -4f TO 406f
- 25% CARBON PTFE SEATS
- 90 DEGREE V-PORT BALL
- NACE MR 017/ISO 15156 AND NACE MR 0103 COMPLIANT

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING. \*ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.\*

NOTE: FORMERLY S90V SERIES



DRAWING NAME:

12V ELECTRIC ACTUATED STAINLESS STEEL 2-WAY 2" 90 DEGREE V-PORT 1000 PSI BALL VALVE WITH 4-20mA POSITIONING

|                 |           |                                      |           |
|-----------------|-----------|--------------------------------------|-----------|
| MATERIAL:<br>-- | A         | DRAWING NUMBER:<br>E012D42-S3FV90-16 | REV.<br>3 |
| SCALE: N.T.S.   | NAME: MCH | DATE: 3/5/2019                       |           |