



VALVE NOTES:

- STAINLESS STEEL - PEICE
- 1000 PSI (250 STEAM)
- -4f TO 406f
- 25% CARBON PTFE SEATS
- 90 DEGREE V-PORT BALL
- NACE MR 017/ISO 15156 AND NACE MR 0103 COMPLIANT

ACTUATOR:

- DOUBLE ACTING, 80 PSI MINIMUM OPERATING PSI.

POSITIONER

- (M3 OPTION) INPUT CONTROL 3-15 PSI
- (M4 OPTION) INPUT CONTROL 4-20mA
(0-10 Input also available, consult factory).
- 1/4" NPT INPUT PORT
- PRESSURE GAUGE INCLUDED (NOT SHOWN)
- VISUAL INDICATOR (TOP)

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



DRAWING NAME:

2" NPT 1000 PSI SS PNEUMATIC ACTUATED V-PORT
BALL VALVE W.90 DEGREE V PORT AND POSITIONING

MATERIAL:	A	DRAWING NUMBER: PD-SV90-16-M*	REV. 2
SCALE: N.T.S.	NAME: MCH	DATE: 5/2/2019	