



ACTUATOR NOTES

HOUSING MATERIAL	HIGH IMPACT PLASTIC
RATINGS/CERTIFICATIONS	IP67
OPERATING TEMP	-4°F TO 131°F
TORQUE	530 IN/LBS (60 Nm)
0° TO 90° CYCLE TIME	9 SEC.
VOLTAGES AVAILABLE:	12 VAC/DC 2.8-3.8 AMP
	24VAC/DC 1.2-1.8 AMP
	100-240 VAC 0.3-0.6 AMP
LIMIT SWITCHES	2 INTERNAL, STANDARD
INTERNAL HEATER	STANDARD FEATURE
BATTERY BACKUP FAILSAFE	OPTIONAL
4-20mA FEEDBACK	OPTIONAL

DUTY CYCLE: 24V,110V,220V=75%. (12V=50%)



DRAWING NAME:
60 SERIES ELECTRIC ACTUATOR:
(12VAC/DC, 24 VAC/DC, 110-240 VAC)

MATERIAL:	A	DRAWING NUMBER: VB060-0XX	REV. 2
SCALE: N.T.S.	NAME: MCH	DATE: 10-28-20	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS
EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.